

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1. **(Currently Amended)** A light source apparatus for a vehicle headlight, comprising:
 - a base;
 - a plurality of LED elements located adjacent the base; and
 - a light shielding device located adjacent the base and formed in the shape of a light distribution pattern, wherein the LED elements are arranged in such a manner as to correspond to the shape of the light shielding device, and in such a manner as to form an emission shape suited for a light distribution pattern for a vehicle headlight, **and at least some of the LED elements are arranged along a given ridgeline.**
2. **(original)** The light source apparatus for a vehicle headlight according to claim 1, wherein each of the LED elements is substantially rectangular in exterior shape.
3. **(original)** The light source apparatus for a vehicle headlight according to claim 1, wherein each of the LED elements is substantially triangular in exterior shape.
4. **(original)** The light source apparatus for a vehicle headlight according to claim 1, wherein at least one of the LED elements is different in size as compared to another of the LED elements.
5. **(Currently Amended)** A light source apparatus for a vehicle headlight comprising:
 - a base;

a plurality of LED elements located adjacent the base, wherein the LED elements are arranged in such a manner as to form an emission shape suited for a light distribution pattern for a vehicle headlight, **wherein at least some of the LED elements are arranged along a given ridgeline;** and

a drive device capable of supplying different drive currents to the LED elements, wherein at least one of the LED elements is driven by a different drive current as compared to another of the LED elements.

6. (canceled)

7. (currently amended) The light source apparatus for a vehicle headlight according to claim 1, wherein at least **some another** of the LED elements **are is** arranged along **a second ridgeline** ~~two linear ridgelines~~.

8. (currently amended) The light source apparatus for a vehicle headlight according to claim 7, wherein the ~~two linear ridgelines~~ **given ridgeline and the second ridgeline** are at a given angle with respect to each other, and the given angle is between approximately 15 and 45 degrees.

9. (original) The light source apparatus for a vehicle headlight according to claim 1, wherein the base includes at least one cavity and the plurality of LED elements are mounted in the at least one cavity located in the base.

10. (original) The light source apparatus for a vehicle headlight according to claim 1, wherein each of the LED elements is arranged in such a manner as to form a brightness distribution suitable for a vehicle headlight.

11. **(cancelled)**
12. **(original)** The light source apparatus for a vehicle headlight according to claim 1, wherein each of the LED elements is substantially parallelogrammic in exterior shape.
13. **(previously presented)** A vehicle headlight, comprising:
the light source apparatus according to claim 1; and
a projection lens arranged such that a focus of the projection lens located in the direction of the light source apparatus is located in the vicinity of the light shielding device, wherein the projection lens is configured to irradiate forward the shape of an emission portion of the light source apparatus cut off by the light shielding device.
14. **(original)** A light source, comprising:
a base;
a plurality of LED elements located adjacent the base and formed in a non-symmetrical array such that light emitted from the LED elements forms a light distribution pattern.
15. **(original)** The light source according to claim 14, wherein each of the LED elements is substantially rectangular in exterior shape.
16. **(original)** The light source according to claim 14, wherein each of the LED elements is substantially triangular in exterior shape.
17. **(original)** The light source according to claim 14, wherein at least one of the LED elements is different in size as compared to another of the LED elements.
18. **(original)** The light source according to claim 14, further comprising:

a drive device capable of supplying different drive currents to the LED elements, wherein at least one of the LED elements is driven by a different drive current as compared to another of the LED elements.

19. **(original)** The light source according to claim 14, further comprising:
a resin formed on a top surface of the base and over the LED elements.
20. **(original)** The light source according to claim 14, wherein the LED elements are arranged in two linear rows, the rows being arranged at a given angle with respect to each other, and the given angle is between approximately 15 and 45 degrees.
21. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 1, wherein each of the LED elements is substantially square in exterior shape.
22. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 14, wherein the base includes at least one cavity and the plurality of LED elements are mounted in the at least one cavity located in the base.
23. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 5, wherein at least one of the LED elements is different in size as compared to another of the LED elements.
24. **(previously presented)** A vehicle headlight, comprising the light source apparatus according to claim 5, and
a projection lens arranged such that a focus of the projection lens located in a direction of the light source apparatus is located on an optical axis of the light source apparatus.

25. **(previously presented)** A vehicle headlight, comprising the light source apparatus according to claim 14, wherein
- a portion of the LED elements is formed on a ridgeline, and
 - a projection lens is configured such that a focus of the projection lens is located on the ridgeline.
26. **(currently amended)** A vehicle headlight, comprising the light source apparatus according to claim 7, and
- a projection lens arranged such that a focus of the projection lens located in a direction of the light source apparatus is located in the vicinity of an intersection of the ~~two linear ridgelines~~ given ridgeline and the second ridgeline.
27. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 1, wherein at least one of the LED elements is polygonal in exterior shape.
28. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 5, wherein at least one of the LED elements is parallelogrammic in exterior shape.
29. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 5, wherein at least one of the LED elements is substantially square in exterior shape.
30. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 14, wherein at least one of the LED elements is parallelogrammic in exterior shape.
31. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 14, wherein at least one of the LED elements is substantially square in exterior shape.

32. **(previously presented)** The light source apparatus for a vehicle headlight according to claim 14, wherein at least one of the LED elements is substantially polygonal in exterior shape.

33. **(new)** The light source apparatus for a vehicle headlight according to claim 14, wherein the light source apparatus has an optical axis located at a position in the substantial center of the array of LED elements and along which light is directed from the LED elements, and the array of LED elements is non-symmetrical about the optical axis.

34. **(new)** The light source apparatus for a vehicle headlight according to claim 14, wherein at least some of the LED elements are located along a ridgeline.